



Monocoat.us

www.monocoat.us

info@monocoat.us

1 (877) 928-9663

CREATIVE EFFECTS - SMOKE

DESCRIPTION:

Monocoat Smoke has been especially developed to provide an ammonia-smoked aspect to oak. This product reacts in accordance to the amount of tannic acid that is present in the wood. When treated with **Monocoat Smoke**, oak will age. The treatment allows you to create very unique effects since the darkness of the aging depends on the amount of tannin in the wood.

Monocoat Smoke is user friendly and does not release any toxic or irritating fumes or vapors. The product is designed to be post treated with **Monocoat Oil Plus**.

Attention: Variations in the final result can be expected depending on the quality and origin of the wood used.

SPECIFIC CHARACTERISTICS:

- Can be post-treated with **Monocoat Oil Plus**.
- Provides a similar aspect as an ammonia-smoking treatment.
- Environmentally friendly, releases no toxic fumes or vapors.

APPLICATION:

- Sand the planks until the desired result has been obtained.
- Remove all dust from the surface.
- Apply **Monocoat Smoke** evenly with a paint roller, brush or spray gun.
- Once the wood dries, wash off the surface with water. Damp mopping or washing with clean dampened cloths is all right.
- Allow the wood to completely dry.
- Remove the raised grain by polishing the surface with a buffer and a red or beige pad.
- Make sure the surface is made fully dust-free again.
- Apply **Monocoat Oil Plus**.

TECHNICAL CHARACTERISTICS:

Physical state at 68 °F:	liquid
Color:	colorless
Odor:	specific
pH:	12-13

CONSUMPTION:

Depending on the method of preparation and the type of wood: +/- 175 to 400 sq. ft/liter.

STORAGE:

The product can be stored for up to 6 months in dry conditions in the original packaging. Do not allow freezing.

PACKAGE:

250 ml, 1 liter, 5 liter jugs.